

Kilfrost DF Plus (88)[®] Dilute - Ready to Use, 63/37

MATERIAL SAFETY DATA SHEET



1. PRODUCT NAME & DESCRIPTION

Kilfrost DF Plus (88)[®] Dilute - Ready to Use, 63/37

Aircraft Deicing fluid, Type I
Complies with Specification ISO 11075 and AMS 1424

MANUFACTURED AND SUPPLIED IN THE USA BY

Cryotech Deicing Technology
6103 Orthoway
Fort Madison, IA 52627
United States

Cryotech Contact Information

Telephone: (800)346-7237
FAX: (319)372-2662
email: deicers@cryotech.com
website: <http://www.cryotech.com>

MANUFACTURED AND SUPPLIED IN EUROPE BY

Kilfrost Limited
Albion Works, HALTWHISTLE
Northumberland, NE49 0HJ
ENGLAND

Kilfrost Contact Numbers (direct dial from USA)

Working hours: (011)(44)1434 321 500
Other Times: (011)(44)1228 573 614
FAX: (011)(44)1434 321 463
email: kilfrost.haltwhistle@virgin.net

2. CHEMICAL COMPOSITION

Aqueous monopropylene glycol mixture.
Contains a minimum of 55% monopropylene glycol (CAS 57-55-6)

3. HAZARD IDENTIFICATION

RESPIRATORY/INHALATION: Considered to be non-hazardous.

SKIN IRRITATION: Unlikely to cause irritation.

EYE CONTACT: May cause temporary irritation.

INGESTION: Considered to be non-hazardous.

OCCUPATIONAL EXPOSURE LIMITS:

An exposure limit has been set for Monopropylene Glycol (synonym Propane-1,2-diol). This applies to the UK only.

UK (EH 40) OES

Total (vapor & Particulates)		150 ppm (10 mg/m ³)(8hr TWA)
Particulates		- ppm (10 mg/m ³)(8hr TWA)
ACGIH	TLV - TWA	No limit assigned.
FRANCE	VME	No limit assigned.
GERMANY	MAK	No limit assigned.

4. FIRST AID MEASURES

Chemical Emergency: Spill, leak, fire, or accident call
Chemtrec day or night (800)424-9300;
Outside continental USA call (703)527-3887

EYE CONTACT: Flush eyes immediately with fresh water for least 15 minutes while holding eyelids open. Consult medical personnel if irritation persists

SKIN CONTACT: Wash off in flowing water. Launder contaminated clothing before re-use.

INHALATION: Remove to fresh air if feeling unwell. Consult medical personnel if symptoms persist.

INGESTION: Give large quantities of water to drink. Consult medical personnel.

5. FIRE FIGHTING MEASURES

FLASH POINT (close cup): None below boiling point.

AUTO IGNITION: 446°C

EXPOSURE LIMITS: No data.

EXTINGUISHING MEDIA: Water, foam, Carbon Dioxide, dry powder.

FIRE FIGHTING PROCEDURES: None

HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce Carbon Monoxide and other harmful gases/vapors.

UNUSUAL FIRE HAZARDS: The product may become combustible after prolonged heating at the boiling point.

NFPA RATINGS:

Health 0; Flammability 1; Reactivity 0; Special NDA:

(Least - 0, Slight - 1, Moderate - 2, High - 3, Extreme - 4)

These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint Coating Association.

6. ACCIDENTAL RELEASE MEASURES

Chemical Emergency: Spill, leak, fire, or accident call

Chemtrec day or night (800)424-9300;

Outside continental USA call (703)527-3887

SPILL/LEAK PRECAUTIONS:

Contain spillage and absorb on suitable material e.g. sawdust, sand or earth. Transfer to a container for disposal. See section 13.
Wash the spillage area with plenty of water.

7. HANDLING AND STORAGE

STORAGE: Store in tightly sealed original containers, away from direct heat and strong oxidizing agents.

SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing mists/vapors when spraying.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear eye protection if splashing is possible. An eye wash bottle should be available.

SKIN PROTECTION: Gloves and protective overalls recommended if prolonged contact is likely.

VENTILATION: Maintain sufficient ventilation to comply with 'Occupational Exposure Standard'.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, orange fluid.

ODOR: None

pH (20°C): 7.5-8.5

BOILING POINT: ~106°C

FLAMMABILITY DATA: See Section 5

VAPOR PRESSURE (20°C): 13 mm Hg

SPECIFIC GRAVITY (20°C): 1.041

VAPOR DENSITY (AIR = 1): No data

FREEZING POINT: -43.5°C (-46.3°F)

VISCOSITY:

20°C	10 mPas
0°C	26 mPas
-20°C	166 mPas

SPECIFIC HEAT:

20°C	3.5 J/g/°C
70°C	3.6 J/g/°C

SOLUBILITY IN WATER: Completely miscible.

Kilfrost DF Plus (88)[®] Dilute - Ready to Use, 63/37

MATERIAL SAFETY DATA SHEET

<p>10. STABILITY & REACTIVITY Stable under normal storage conditions. Incompatible materials - strong oxidizing agents.</p>	<p>15. REGULATORY INFORMATION DOT SHIPPING NAME: Not designated as a hazardous material by the Federal DOT. DOT HAZARD CLASS: Not Applicable DOT IDENTIFICATION NUMBER: Not Applicable SARA 311 CATEGORIES: 1. Immediate (Acute) Health Effects: Yes 2. Delayed (Chronic) Health Effects: No 3. Fire Hazard: No 4. Sudden Release of Pressure Hazard: No 5. Reactivity Hazard: No REGULATORY LISTS SEARCHED: 01 = SARA 313 02 = MASS RTK 03 = NTP Carcinogen 04 = CA Prop. 65 05 = MI 406 06 = IARC Group 1 07 = IARC Group 2A 08 = IARC Group 2B 09 = SARA 302/304 10 = PA RTK 11 = NJ RTK 12 = CERCLA 302.4 13 = MN RTK 14 = ACGIH TLV 15 = ACGIH STEL 16 = ACGIH Calculated TLV 17 = OSHATWA 18 = OSHA STEL 20 = EPA Carcinogen 21 = TSCA Sect 4(e) 22 = TSCA Sect 5(a)(e)(f) 23 = TSCA Sect 6 24 = TSCA Sect 12(b) 25 = TSCA Sect 8(a) 26 = TSCA Sect 8(d) 27 = TSCA Sect 8(f) 28 = Canadian WHMIS 29 = OSHA CEILING The ingredient mono-propylene glycol appears on the above regulatory lists 10, 13 and 28. None of the other components of this material are found on the regulatory lists indicated.</p>
<p>11. TOXICOLOGICAL INFORMATION Considered to have low oral toxicity. See also section 3 LD₅₀ rat - oral >10g/Kg (est.) LC₅₀ Pimephales Promelas 7,650 mg/L (96h)(est) LC₅₀ Daphnia Magnia >10,000 mg/L (48h)(est)</p>	<p>16. OTHER INFORMATION All components are registered in accordance with EINECS AND TSCA. This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community right-to-know/emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS. Discard any previous edition of this MSDS. Latest version of this MSDS can be found at http://www.cryotech.com</p>
<p>12. ECOLOGICAL INFORMATION COD: 0.9 kg O₂/kg fluid (est) BOD₅: 0.6 kg O₂/kg fluid (est) 5 day BOD/COD: 0.6 (est)</p>	
<p>13. DISPOSAL CONSIDERATION Controlled incineration or landfill in accordance with local, state or national regulations.</p>	
<p>14. TRANSPORT INFORMATION Not restricted under any transport regulations.</p>	

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, **Cryotech Deicing Technology, a Division of General Atomics International Services Corporation makes no warranty, either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon.** Cryotech Deicing Technology, a Division of General Atomics International Services Corporation assumes no responsibility for any injury or loss resulting from the use of the product described herein. User should satisfy himself that he has all current data relevant to his particular use.