



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 1 – IDENTIFICATION

PRODUCT IDENTIFIER

Polar Plus® LT
55/45 DILUTE – Ready to Use
(Consisting of 55% Polar Plus LT and 45% water)
Type I Aircraft Deicing / Anti-icing Fluid
Complies with Specification AMS 1424/1

OTHER MEANS OF IDENTIFICATION

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Deicing/Anti-icing aircraft

RESPONSIBLE PARTY INFORMATION

Name/Address

Cryotech Deicing Technology
6103 Orthoway
Fort Madison, IA 52627
United States

Contact information

Telephone: (800) 346-7237
Email: deicers@cryotech.com
Website: www.cryotech.com

EMERGENCY PHONE NUMBER

CHEMTREC: (800) 424-9300
Outside USA and Canada: (703) 741-5970

SECTION 2 – HAZARD IDENTIFICATION

HAZARD INFORMATION ACCORDING TO OSHA HAZCOM 2024

| | |
|----------------------------------|-----------------------------|
| Hazard classification | Not classified as hazardous |
| Signal word | N/A |
| Hazard statement(s) | N/A |
| Hazard symbol(s) | No pictogram |
| Precautionary statement(s) | Not required |
| Hazards not otherwise classified | None |

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES

| Chemical Name | Common name and synonyms | CAS number | %(wt.) |
|--------------------------------------|--------------------------|------------|--------|
| Propane-1,2-diol | Propylene glycol | 57-55-6 | 48 |
| Water | | 7732-18-5 | 52 |
| Trade secret/proprietary ingredients | | | <1 |



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURE

| | |
|-------------------|---|
| Inhalation | If inhaled, remove to fresh air. Get medical advice if cough or other symptoms appear. |
| Skin | Wash hands and exposed skin thoroughly after handling |
| Eye | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention |
| Ingestion | If swallowed, give milk or water to drink and telephone for medical advice. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person |

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

May cause temporary minor eye or skin irritation. Inhalation of mist during handling may cause minor respiratory tract irritation and coughing.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

If you feel unwell, seek medical advice. Treat symptomatically.

SECTION 5 – FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Water spray, carbon dioxide, or dry chemical. Use extinguishing media appropriate for the surrounding environment.

UNSUITABLE EXTINGUISHING MEDIA

Not applicable

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Heat from fire can generate flammable vapor. Vapor is heavier than air and may spread along floors. Pressure buildup in sealed containers in high heat conditions may cause container to rupture.

Products of combustion: oxides of carbon

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Wear protective equipment suitable for the surrounding environment.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Avoid eye/skin contact. Avoid breathing mist. Wear appropriate personal protective equipment (refer to Section 8 of this SDS). Wash hands thoroughly after use. Change contaminated clothing.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Contain and/or absorb spill with inert material (e.g., sand, vermiculite), then place in a suitable container. Use appropriate Personal Protective Equipment (PPE).

Scoop up material and place in a disposable container.



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Avoid eye/skin contact. Avoid breathing mist. Wear appropriate personal protective equipment (refer to Section 8 of this SDS). Wash hands thoroughly after use. Change contaminated clothing.

PRECAUTIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store in tightly sealed original UV resistant containers, away from direct heat and strong oxidizing agents. Product should not be stored in semi-transparent containers.

Temperature Storage Limits: Minimum -18°F (-28°C)
 Maximum 140°F (60°C)

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

US OSHA PERMISSIBLE EXPOSURE LIMIT (PEL)

No specific limits established.

AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS THRESHOLD LIMIT VALUE (TLV)

No TLV established.

AMERICAN INDUSTRIAL HYGIENE ASSOCIATION (AIHA)

Workplace Environmental Exposure Level (WEEL) for Propane-1,2-diol (CAS: 57-55-6): 8-hr Time-weighted Average (TWA): 10 mg/m³

APPROPRIATE ENGINEERING CONTROLS

Have eyewash stations available. Ensure adequate ventilation if handling in confined areas.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Safety glasses or goggles are recommended if splashing/spraying is possible.

Skin/Hand Protection: No special skin protection is usually necessary. Chemical resistant gloves should be worn if prolonged exposure is possible to prevent drying of skin.

Respiratory Protection: No special respiratory protection is usually necessary. Breathing of mist/aerosol should be avoided. If operating conditions create high airborne concentrations of this material, the use of an approved respirator is recommended.

Always use good personal hygiene habits when using this product, such as avoiding touching the face, and thoroughly and regularly washing hands.



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------------------|---|
| Physical State | Clear liquid |
| Color | Orange |
| Odor | Odorless (Odor threshold not available) |
| Melting point/freezing point | <-28°F(<-33°C) |
| Boiling point | ~220°F (105°C) |
| Flammability | Not flammable |
| Explosive limits (lower and upper) | Data not available |
| Flash point | > 212°F (100°C) based on propylene glycol |
| Auto-ignition temperature | > 750°F (400°C) based on propylene glycol |
| Decomposition temperature | Data not available |
| pH | 7.5 – 9.0 |
| Viscosity | <10 cP at 20°C |
| Solubility | Completely miscible in water |
| Partition coefficient n-octanol/water | Data not available |
| Vapor pressure | ~15 mm Hg |
| Relative density | 1.039 |
| Relative vapor density | Data not available |
| Particle characteristics | Not applicable |

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY

This product is expected to be non-reactive under normal conditions of use, storage, and transport.

CHEMICAL STABILITY

Stable under normal storage conditions. Polymerization will not occur.

POSSIBILITY OF HAZARDOUS REACTIONS, INCLUDING THOSE ASSOCIATED WITH FORESEEABLE EMERGENCIES

No dangerous reactions known under conditions of normal use.

CONDITIONS TO AVOID

Avoid prolonged exposure to temperatures over the boiling point of water. When water has evaporated, remaining material is combustible.

INCOMPATIBLE MATERIALS

Strong oxidizing agents; strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

May decompose into oxides of carbon (e.g., CO, CO₂).



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 11 – TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

Ingestion is unlikely during normal operations. Inhalation of material is most likely when in confined areas or during spraying operations. Skin contact may occur from spraying operations. Eye contact is possible from touching eyes with contaminated hands.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL, AND TOXICOLOGICAL CHARACTERISTICS

Corneal injury is unlikely. Inhalation of material during handling may cause temporary respiratory tract irritation and coughing. Unlikely to cause significant skin irritation. Not expected to cause significant health effects by accidental ingestion.

DELAYED AND IMMEDIATE EFFECTS AND CHRONIC EFFECTS FROM SHORT- AND LONG-TERM EXPOSURE

This product is not expected to produce serious delayed or chronic effects from short- or long-term exposure.

NUMERICAL MEASURES OF TOXICITY

LD50 rat-oral: > 15 g/kg (estimated from studies of components)

INTERACTIVE EFFECTS

None known.

CARCINOGENIC INFORMATION

No component in this product is listed in the National Toxicology Program (NTP) Report on Carcinogens or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs or by OSHA.

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICITY

Not expected to cause long-term adverse effects in the aquatic or terrestrial environments.

| | | |
|------|---------------------|-------------------------|
| LC50 | Pimephales promelas | 45,500 mg/L (undiluted) |
| LC50 | Daphnia magna | 28,000 mg/L (undiluted) |
| LC50 | Ceriodaphnia dubia | 21,800 mg/L (undiluted) |

PERSISTENCE AND DEGRADABILITY

Readily biodegradable.

| | |
|--------------------------|--|
| COD: | 0.89 g O ₂ /g deicer (calculated) |
| BOD ₅ (20°C): | 0.31 g O ₂ /g deicer (calculated) |
| 5 day BOD/COD: | 0.35 |

BIOACCUMULATIVE POTENTIAL

Data not available

MOBILITY IN SOIL

Data not available

OTHER ADVERSE EFFECTS

None expected.



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE RESIDUES AND INFORMATION ON SAFE HANDLING AND METHODS OF DISPOSAL

Based on available information, this product is neither listed as a hazardous waste nor does it exhibit any of the characteristics that would cause it to be classified as a characterized hazardous waste under the US Resource Conservation and Recovery Act (RCRA). If product should spill or be otherwise unsuitable for normal deicing operations, dispose of contents/container in accordance with local, state, regional, national, and/or international regulations.

SECTION 14 – TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| UN number | Not applicable. This material is not regulated as dangerous per US DOT or IATA/ICAO. |
| UN proper shipping name | Not applicable |
| Transport hazard class(es) | Not applicable |
| Packing group | Not applicable |
| Environmental hazards | Not applicable. This material is not a Marine pollutant. |
| Transport in bulk | Consult IMO regulations before transporting ocean bulk. |
| Special precautions | Not applicable |

SECTION 15 – REGULATORY INFORMATION

INVENTORY LISTS

All of the components in this product are on the following inventory lists: US (TSCA), Canada (DSL/NDSL), Europe (EINECS); or not required to be listed.

TSCA SECTION 12(B)

None of the chemicals in this product are listed under US EPA Toxic Substances Control Act (TSCA) Section 12(b).

CERCLA HAZARDOUS SUBSTANCES

This material, as supplied, does not contain any chemicals regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302). There is no CERCLA Reportable Quantity for this material. There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT (EPCRA) SECTION 313

None of the chemicals in the product are subject to reporting under the US EPA Toxics Release Inventory (TRI) program.

HAZARD CATEGORIES FOR EPCRA 311 / 312

| Health hazard | |
|---|----|
| Carcinogenicity | No |
| Acute toxicity (any route of exposure) | No |
| Aspiration hazard | No |
| Reproductive toxicity | No |
| Germ cell mutagenicity | No |
| Skin corrosion or irritation | No |
| Respiratory or skin sensitization | No |
| Serious eye damage or eye irritation | No |
| Specific organ toxicity (single or repeated exposure) | No |
| Simple asphyxiant | No |
| Hazard not otherwise classified (HNOC) | No |

| Physical hazard | |
|--|----|
| Flammable (gases, aerosols, liquids or solids) | No |
| Gas under pressure | No |
| Explosive | No |
| Self-heating | No |
| Pyrophoric (liquid or solid) | No |
| Pyrophoric gas | No |
| Oxidizer (liquid, solid or gas) | No |
| Organic peroxide | No |
| Self-reactive | No |
| In contact with water emits flammable gas | No |
| Combustible dust | No |
| Corrosive to metal | No |



Polar Plus® LT
55/45 DILUTE
Type I Aircraft Deicing / Anti-icing Fluid
Safety Data Sheet


| |
|--|
| Hazard not otherwise classified (HNOC) |
|--|

| |
|----|
| No |
|----|

CLEAN WATER ACT

None of the chemicals in this product are listed as Priority Pollutants under the US EPA CWA.
None of the chemicals in this product are listed as Toxic Pollutants under the US EPA CWA.

NFPA 704



SECTION 16 – OTHER INFORMATION

SDS REVISION DATE

This SDS was revised on **September 9, 2025**

The latest version can be obtained by contacting Cryotech Deicing Technology.

DISCLAIMER

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology makes no warranty, either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology assumes no responsibility for any injury or loss resulting from the use of the product described herein. User should satisfy himself that he has all current data relevant to his particular use.

End of Safety Data Sheet