



# Polar Plus® LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

Safety Data Sheet

### Section 1: IDENTIFICATION

#### PRODUCT IDENTIFIER

**Polar Plus® LT**

50/50 DILUTE – Ready to Use

(Consisting of 50% Polar Plus LT and 50% water)

Type I Aircraft Deicing / Anti-icing Fluid

Complies with Specification AMS 1424/1

#### RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Deicing / Anti-icing aircraft

#### DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

**Name/Address**

Cryotech Deicing Technology

6103 Orthoway

Fort Madison, IA 52627

United States

**Contact Information**

Telephone: +1 (800) 346-7237

Fax: +1 (319) 372-2662

Email: [deicers@cryotech.com](mailto:deicers@cryotech.com)

Website: [www.cryotech.com](http://www.cryotech.com)

#### EMERGENCY TELEPHONE NUMBER

CHEMTREC (800) 424-9300

Outside USA and Canada (703) 741-5970

### Section 2: HAZARD(S) IDENTIFICATION

#### CLASSIFICATION ACCORDING TO OSHA HAZCOM 2012

**Hazard Class** Not classified as hazardous

#### LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

There are no OSHA required label elements for this product.

#### CLASSIFICATION ACCORDING TO WHMIS (Canada)

**Hazard Class** Not Classified

**WHMIS Hazard Symbols** Not Applicable

**WHMIS Signal Word** Not Applicable

### Section 3: COMPOSITION/INFORMATION ON INGREDIENT

#### MIXTURES

Ingredient	CAS No	Wt. %
Propylene Glycol	57-55-6	44
Water	7732-18-5	56
Proprietary Ingredients		<1



# Polar Plus® LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

### Safety Data Sheet

#### Section 4: FIRST- AID MEASURES

##### DESCRIPTION OF FIRST-AID MEASURE

<b>Eye</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. If easy to do, remove contact lenses, if worn. No additional first aid should be necessary, however, if irritation persists, get medical attention.
<b>Skin</b>	As a precaution, wash skin thoroughly with soap and water. Remove and wash contaminated clothing.
<b>Inhalation</b>	Not expected to be an inhalation hazard. If inhaled, remove to fresh air. Get medical advice / attention if feeling unwell.
<b>Ingestion</b>	If swallowed, give milk or water to drink. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

##### MOST IMPORTANT SYMPTOMS / EFFECTS

<b>Eye</b>	May be slightly irritating to the eyes. Symptoms may include discomfort or pain, excess blinking, and tear production, with possible redness and swelling.
<b>Skin</b>	May be slightly irritating to the skin. Symptoms may include redness, drying, and cracking of the skin.
<b>Inhalation</b>	Not expected to be an inhalation hazard under normal conditions of use.
<b>Ingestion</b>	Not expected to be an ingestion hazard under normal conditions of use. High doses may cause central nervous system depression.

##### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

<b>Note to Physicians</b>	Treat symptomatically.
<b>Specific Treatments</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

#### Section 5: FIRE-FIGHTING MEASURES

##### FLAMMABILITY

<b>Flammability</b>	Non-flammable by OSHA/WHMIS criteria
---------------------	--------------------------------------

##### EXTINGUISHING MEDIA

<b>Suitable Extinguishing Media</b>	Water spray, alcohol-resistant foam, carbon dioxide, dry chemical.
<b>Unsuitable Extinguishing Media</b>	Do not use solid water stream.

##### SPECIAL HAZARDS

<b>Products of Combustion</b>	May include and are not limited to: oxides of carbon.
<b>Explosion Data</b>	Data not available. Not considered to be an explosion hazard.
<b>Unusual Fire Hazards</b>	Heat from fire can generate flammable vapor.

##### SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA)



# Polar Plus<sup>®</sup> LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

### Safety Data Sheet

#### Section 6: ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

##### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP

**Methods for Containment** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleanup** Scoop up material and place in a disposal container.

#### Section 7: HANDLING AND STORAGE

##### PRECAUTIONS FOR SAFE HANDLING

**Handling** Avoid contact with skin and eyes. Avoid breathing mists and vapors when spraying.

**General Hygiene Advice** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

##### PRECAUTIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Storage** Store in tightly sealed original UV resistant containers, away from direct heat and strong oxidizing agents. Product should not be stored in clear or semi-transparent containers.

**Temperature Storage Limits** Minimum -22°C (-7°F)  
Maximum 60°C (140°F)

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### EXPOSURE LIMITS

Ingredient	OSHA PEL	ACGIH-TLV
None Listed	----	----

##### EXPOSURE CONTROLS

**Engineering Controls** No special ventilation is necessary.

##### INDIVIDUAL PROTECTIVE MEASURES/PERSONAL PROTECTIVE EQUIPMENT

##### Personal Protective Equipment

**Eye/Face Protection** Safety glasses or goggles are recommended if splashing / spraying is possible.

**Skin Protection/Hand Protection** No special skin protection is usually necessary. Chemical resistant gloves should be worn if prolonged exposure is possible to prevent drying of skin.

**Respiratory Protection** No special respiratory protection is usually necessary. Breathing of mist/aerosol should be avoided. If operating conditions create high airborne concentrations of this material, the use of an approved respirator is recommended.



# Polar Plus<sup>®</sup> LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

### Safety Data Sheet

**General Health and Safety Measures** Do not eat, smoke or drink where material is handled, processed, or stored. Wash hands carefully before eating or smoking. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Section 9: PHYSICAL AND CHEMICAL PROPERTIES

##### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Clear, orange liquid
<b>Color</b>	Orange
<b>Odor</b>	None
<b>Odor Threshold</b>	Not available
<b>Physical State</b>	Liquid
<b>pH (20°C)</b>	7.5 – 9.0
<b>Melting Point / Freezing Point</b>	<-27°C (<-17°F)
<b>Initial Boiling Point and Boiling Range</b>	~105°C (220°F)
<b>Flash Point</b>	>100°C (212°F)
<b>Evaporation Rate</b>	Not available
<b>Flammability</b>	Not available
<b>Lower Flammability/Explosive Limit</b>	Not available
<b>Upper Flammability / Explosive Limit</b>	Not available
<b>Vapor Pressure (20°C)</b>	~15mm Hg
<b>Vapor Density</b>	No Data Available
<b>Relative Density/Specific Gravity (20°C)</b>	1.037
<b>Solubility</b>	Miscible in water
<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Auto-ignition Temperature</b>	>400°C (750°F)
<b>Decomposition Temperature</b>	Not available
<b>Viscosity (20°C)</b>	< 10 cP
<b>Oxidizing Properties</b>	Not available
<b>Explosive Properties</b>	Not available

#### Section 10: STABILITY AND REACTIVITY

##### REACTIVITY

No dangerous reactions known under conditions of normal use.

##### CHEMICAL STABILITY

Stable under normal storage conditions.

##### POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

##### CONDITIONS TO AVOID

High temperatures, contact with incompatible materials.

##### INCOMPATIBLE MATERIALS



# Polar Plus® LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

### Safety Data Sheet

Strong Oxidizers. Strong acids.

#### HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

### Section 11: TOXICOLOGICAL INFORMATION

#### INFORMATION ON TOXICOLOGICAL EFFECTS

<b>Likely Routes of Exposure</b>	Skin contact, eye contact, inhalation, and ingestion.
<b>Symptoms related to physical/chemical/toxicological characteristics</b>	
<b>Eye</b>	May cause eye irritation. Symptoms may include discomfort or pain, excess blinking, and tear production, with possible redness and swelling.
<b>Skin</b>	May cause skin irritation. Symptoms of prolonged contact may include redness, drying and cracking of the skin.
<b>Ingestion</b>	Not expected to be an ingestion hazard. Ingestion of large doses may cause central nervous system depression.
<b>Inhalation</b>	Not expected to be an inhalation hazard under normal conditions of use.
<b>Acute Toxicity</b>	LD50 rat-oral: >22 g/kg

#### DELAYED, IMMEDIATE EFFECTS AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

<b>Skin Corrosion / Irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious Eye Damage/Irritation</b>	Based on available data, the classification criteria are not met.
<b>Respiratory Sensitization</b>	Based on available data, the classification criteria are not met.
<b>Skin Sensitization</b>	Based on available data, the classification criteria are not met.
<b>STOT-Single Exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-Repeated Exposure</b>	Based on available data, the classification criteria are not met.
<b>Germ Cell Mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	This product does not contain any ingredients that are considered to be carcinogens by IARC, NTP or OSHA.
<b>Reproductive Toxicity</b>	Based on available data, the classification criteria are not met.
<b>STOT-Single Exposure</b>	Based on available data, the classification criteria are not met.
<b>STOT-Repeated Exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration Hazard</b>	Based on available data, the classification criteria are not met.

### Section 12: ECOLOGICAL INFORMATION

#### ECOTOXICITY (AQUATIC AND TERRESTRIAL)

<b>Acute/Chronic Toxicity</b>	Not expected to cause long-term adverse effects in the aquatic environment.		
<b>LC50</b>	Pimephales promelas	45,400 mg/L (undiluted)	
<b>LC50</b>	Daphnia magna	28,000 mg/L (undiluted)	
<b>LC50</b>	Ceriodaphnia dubia	21,800 mg/L (undiluted)	

#### PERSISTENCE AND DEGRADABILITY

Readily biodegradable.

COD	0.81 g O <sub>2</sub> /g deicer (calculated)
BOD <sub>5</sub> (20°C)	0.29 g O <sub>2</sub> /g deicer (calculated)
5 day BOD/COD:	0.35

#### BIOACCUMULATIVE POTENTIAL

Bioaccumulation is not expected.

#### MOBILITY IN SOIL



# Polar Plus® LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

### Safety Data Sheet

Not available.

#### OTHER ADVERSE EFFECTS

Not available.

### Section 13: DISPOSAL CONSIDERATIONS

#### WASTE TREATMENT AND METHODS OF DISPOSAL

Based on available information this product is neither listed as a hazardous waste nor does it exhibit any characteristics that would cause it to be classified as a RCRA hazardous waste. If product should spill or be otherwise unsuitable for normal deicing applications, it may be absorbed onto suitable materials and disposed of in a sanitary landfill unless local, state or provincial regulations prohibit such disposal.

### Section 14: TRANSPORT INFORMATION

#### TRANSPORT INFORMATION

Not regulated as dangerous goods per US DOT or IATA.

### Section 15: REGULATORY INFORMATION

#### INVENTORY LISTS

All of the components in this product are on the following inventory lists: USA (TSCA), Canada (DSL/NDSL), Europe (EINECS)

#### TSCA SECTION 12(b)

None of the chemicals in this product are listed under TSCA Section 12 (b)

#### CERCLA HAZARDOUS SUBSTANCES

There is no CERCLA Reportable Quantity for this material.

#### SARA 311/312 CATEGORIES

Physical hazards		Health hazards	
Explosive	No	Acute toxicity (any route of exposure)	No
Flammable (gases, aerosols, liquids or solids)	No	Skin corrosion or irritation	No
Oxidizer (liquid, solid or gas)	No	Serious eye damage or eye irritation	No
Self- reactive	No	Respiratory or skin sensitization	No
Pyrophoric (liquid or solid)	No	Germ cell mutagenicity	No
Pyrophoric Gas	No	Carcinogenicity	No
Self-heating	No	Reproductive toxicity	No
Corrosive to metal	No	Specific target organ toxicity (single or repeated exposure)	No
Gas under pressure (compressed gas)	No	Aspiration hazard	No
In contact with water emits flammable gas	No	Simple Asphyxiant	No
Combustible Dust	No	Hazard Not Otherwise Classified (HNOC)	No
Hazard Not Otherwise Classified (HNOC)	No		

Prepared According to the OSHA Hazard Communication Standard (29 CFR 1910.1200)  
by Cryotech Deicing Technology, 6103 Orthoway, Fort Madison, IA 52627

Form #MKT6010 Rev. August 1, 2021



# Polar Plus® LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid Safety Data Sheet

### SARA 313

None of the components in this product are subject to reporting under SARA Section 313.

### CLEAN WATER ACT

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

### STATE RIGHT-TO-KNOW

This product does not contain components at levels which are required to be reported under the statutes of the following states: MA

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

Component	CAS Number	Amount
Propylene Glycol	57-55-6	44%

This product contains the following chemicals regulated by Pennsylvania Right to Know Act:

Component	CAS Number	Amount
Propylene Glycol	57-55-6	44%

This product may contain the following materials known to the State of California (Proposition 65) to cause cancer, birth defects, or other reproductive harm:

Component	CAS Number	Amount
Ethylene Oxide	75-21-8	< 0.001 ppm
Propylene Oxide	75-56-9	< 0.001 ppm

1,4 Dioxane	123-91-1	< 0.001 ppm
-------------	----------	-------------

#### NFPA - National Fire Protection Association

Health: 0

Fire: 1

Reactivity: 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

#### HMIS - Hazardous Materials Identification System

Health: 0

Fire: 1

Physical Hazard: 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme (\* = chronic hazard)



# Polar Plus<sup>®</sup> LT

50/50 DILUTE

## Type I Aircraft Deicing / Anti-icing Fluid

Safety Data Sheet

---

### Section 16: OTHER INFORMATION

---

**SDS REVISION DATE**                      **August 1, 2021**

**EXPIRATION DATE**                        August 1, 2024

Latest version of this SDS can be obtained from Cryotech.

#### NOTICE TO EMPLOYER

This Safety Data Sheet contains environmental, health, and toxicology information for your employees. Please ensure this information is provided to them. It also contains information to help you meet community right-to-know/emergency response reporting requirements under SARA Title III and many other laws. If you resell this product, this SDS must be given to the buyer or the information incorporated in your SDS. Discard any previous edition of this SDS.

#### DISCLAIMER

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology makes no warranty, either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology assumes no responsibility for any injury or loss resulting from the use of the product described herein. User should satisfy himself that he has all current data relevant to his particular use.

**End of Safety Data Sheet**