

# CRYOTECH CF7® SPECIFICATIONS:

|                               |  |
|-------------------------------|--|
| <b>COMPOSITION</b>            | 50% aqueous potassium acetate solution, by weight,<br>plus corrosion inhibitors  |
| <b>APPEARANCE</b>             | Clear, colorless, mobile liquid, free from matter in suspension  |
| <b>DENSITY</b>                | At 68°F (20°C) = 10.68 lbs/gallon (1.28 g/cm <sup>3</sup> )  |
| <b>VISCOSITY</b>              | At 68°F (20°C) = 10cp maximum<br>At 32°F (0°C) = 20cp maximum  |
| <b>FLASH POINT</b>            | Nonflammable   |
| <b>FREEZING POINT</b>         | -76°F (-60°C)  |
| <b>MISCIBILITY WITH WATER</b> | Complete   |
| <b>STORAGE</b>                | CF7 should not be stored or plumbed through systems that use galvanized, zinc, or brass components                         |
| <b>TYPICAL pH</b>             | 11.0 ± 0.5   |
| <b>SPECIFIC GRAVITY</b>       | At 68°F (20°C) = 1.25 - 1.30   |
| <b>PACKAGING</b>              | 55 gallon drums (208 liters) - (4 minimum)<br>265 gallon tote (1003 liters) - (1 minimum)<br>Bulk - (4400 gallons minimum) |

Revised - 6/09



ISO 9001  
FM 39092



ISO 14001  
EMS 89384



TO ORDER OR FOR PRODUCT INFORMATION CONTACT:  
Ph: +1 319.372.6012 or +1 800.346.7237 Fax: +1 319.372.2662 E-mail: [industrial@cryotech.com](mailto:industrial@cryotech.com)